

**ATTACHMENT B - BID SUBMITTAL FORM**  
**1 Ton Pick-Up Truck – RFB #PUR0817-030**

**SPECIFICATION COMPLIANCE – Any supplier who willfully falsifies responses indicating compliance or non-compliance with the minimum requirements listed below will be subject to suspension and/or debarment from bidding.**

One (1) new 1 Ton Chassis, model year 2017 or 2018

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>Drive Train</b>				
6.0L – 6.7L Gas or Diesel engine, please specify				
84" cab to axle				
Snow Plow Prep Package				
Dual Rear Wheel				
6 Speed Automatic transmission with overdrive				
GVWR 15,000 minimum				
Transmission Power Take Off provision				
Power Steering				
Power four wheel disc anti-lock brakes				
220 AMP alternator				
Transmission Cooler				
Federal Required Emissions				
Heavy Duty batteries				
Power windows/Locks				
Full size spare mounted under bed.				
Anti-spin rear differential, heavy duty				
All season radial tires, black side wall				
Trailer tow package with class IV receiver hitch, 2 weld on D-Rings for Safety Chains. Standard 7 pin wiring connector.				
Four Wheel Drive – Electronic shift on the fly preferred.				
Integrated brake controller				
<b>Interior Components</b>				
Vinyl flooring				
Heated exterior rear view mirrors				
Day/Night interior rear view mirror				
2 extra keys per vehicle, ( <b>Three</b> complete sets of keys and remotes as applicable)				
AM/FM radio w/digital clock, bluetooth				
Gray Cloth Seats				
Rear window electronic defroster				
Driver/Passenger air bags				
Cruise Control				
Side curtain air bag system				
Intermittent windshield wiper system				
Interior trim package to include insulating headliner, full door panels, dome light, vinyl upholstery treated to resist stains.				
Standard tinted windshield				
Air conditioning with all required options				
Tilt steering column				
Electronic speed control				
12V separately fused power port				
Circuit Boss – Circuit Isolator # 70207 (7 circuits), Painless is the current product line we use configured as follows: Circuit 1-3 – constant power Circuit 4-7 - ignition powered				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>Exact connection to particular component will be determined with successful bidder</b>				
Set of four dash mounted body builder/up-fitter switches, mounted within natural reach of driver.				
Weather Tech vinyl floor mats				
<b>Vendor will provide a listing of all filter part numbers</b>				
Vertex VTX609A amber led strobes one on each front corner mounted in headlight pods.				
<b>Body</b>				
Full front bumper				
Chrome Appearance Package				
Manual Folding Telescoping Mirrors				
Fuel filler neck kit, secured to frame or body dependent on configuration				
Engine block heater 110V				
Front Splash Guards				
Cab-chassis rear taillights				
ECCO 510 – 97 db back-up warning beeper				
Day time running lights				
Factory/dealer mounted running boards or tubular steps				
Suspension / Stability Package				
Front Mounted Tow Hooks				
Regular cab				
9' power V front plow with quick hitch mount, plow lights, rubber deflector, and plow side marker flags. 9.2, 9.6 both acceptable, red paint. Boss or Western preferred.				
Full Poly Rear Fender for rear dual wheels With Appropriate Mounting Hardware fixed to frame				
Front Poly Fenders Flares				
Exterior color to be <b>BRIGHT WHITE</b>				
<b>Manuels</b>				
Full set of repair and parts manuals				
<b>Warranty</b>				
Full factory standard warranty				
<b>Electrical Connections</b> all connections must meet this standard minimum				
All lighting used shall be, at a minimum, a two (2) wire light grounded through a wired connection to the battery system.				
Wiring shall be run in loom where exposed, and have grommets or other edge protection where wires pass through metal.				
Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids. Electrical wiring and equipment shall be installed utilizing the following guidelines:				
All wire ends not placed into connectors shall be sealed with a heat shrink end cap. Wires without a terminating connector or sealed end cap shall not be allowed.				
All holes made in the roof shall be caulked with silicon (no exception).				
Corrosion preventative compound shall be applied to non-waterproof electrical connectors located outside of the cab or body. All non-waterproof connections shall require this				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
compound in the plug to prevent corrosion and for easy separation of the plug.				
Any lights containing non-waterproof sockets in a weather-exposed area shall have corrosion preventative compound added to the socket terminal area.				
Rubber coated metal clamps shall be used to support wire harnessing and battery cables routed along the chassis frame rails.				
Heat shields shall be used to protect harnessing in areas where high temperatures exist. Harnessing passing near the engine exhaust shall be protected by a heat shield				
For ease of identification, battery cables shall be color coded. All positive battery cables shall be red in color or wrapped in red loom the entire length of the cable. All negative battery cables shall be black in color				
Wire connections shall be made using crimp style heat shrink butt splice connectors or soldered connection covered with heat shrink. If crimp style connector is used, crimping tool Westward 13H876 or equivalent must be used to prevent piercing heat shrink. Solder sleeve butt splice type connectors shall not be allowed.				

### 9' Steel Dump Body

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>Standards</b>				
Overall length 9'				
Overall width of 86				
7 GA minimum steel construction sides and floor				
12 GA Single walled fold down sides with 6" vertical braces, 12" high				
10 GA Double walled tailgate with vertical bracing, 18" high				
Right side of bulkhead to have a 16" knurled grab handle mounted to be within reach of person accessing the body with the steps.				
3" steel channel cross sills on 16" center (crossmemberless construction is acceptable)				
5" steel channel long sills on 34" center (crossmemberless construction is acceptable)				
Double acting tailgate to drop down/Up and spreader application, tailgate shall include a coal chute				
Sides height 12" to 12.5"				
Quick release one handed lever for easy drop down action on the tailgate.				
Drop Down Sides				
Whelen R1LPPA Top Light Mount to Cab Protector with Ground/power ran from upfitter switch on dash.				
Sub-frame hoist				
Lights to be stop, turn, tail lights LED				
Rear hinged				
Body prop				
Electronic shift PTO				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
Frame mounted hydraulic reservoir with filter and valve				
Hoist Controls mounted in cab				
Buyers Steel 2 rung step 24" high by 12-13" wide. 3'16" by 2" frame, two grip strut 14 gauge minimum steps. Mounted to the passenger side front corner of the dump body at a height so that a 6' tall person can access the lower step with normal leg motion. Steps must be gusset mounted to avoid excessive motion				
10 Gauge Tapered Quarter cab protector with punched window for visibility				
6" amber strobes mounted in rear dump body posts				
Body primed, painted, and rustproofed painted automotive grade high gloss black				

Description	Quantity	Firm Fixed Price
Firm Fixed Price for 1 Ton Chassis with 9' Dump Body per the specifications	1	\$

Cab and Chassis Manufacturer/Model \_\_\_\_\_ Model Year \_\_\_\_\_

9' Steel Dump Body Manufacturer/Model \_\_\_\_\_

Estimated Delivery Time Upon Receipt of Purchase Order \_\_\_\_\_ Calendar Days

Dealer Name \_\_\_\_\_

NOTE: The Bid **MUST** be submitted by a licensed vehicle dealer in the State of Iowa

Dealer Representative Signature \_\_\_\_\_ Date \_\_\_\_\_

**DELIVERY ADDRESS**  
 Joy Huber  
 Fleet Services Division  
 500 15<sup>th</sup> Avenue SW  
 Cedar Rapids, IA 52404

**BILLING ADDRESS**  
 Finance Department – Accounts Payable  
 City of Cedar Rapids  
 101 1<sup>st</sup> Street SE  
 PO Box 2148  
 Cedar Rapids, IA 52406-2148