

ATTACHMENT D - BID SUBMITTAL FORM
¾ Ton Pick-Up Trucks – RFB #PUR0817-030

SPECIFICATION COMPLIANCE – Any supplier who willfully falsifies responses indicating compliance or non-compliance with the minimum requirements listed below will be subject to suspension and/or debarment from bidding.

Two (2) new ¾ Ton Regular Cab Pick-up Trucks, model year 2017 or 2018

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
Drive Train				
6.0L gas engine or greater, V8				
Wheelbase 142"				
GVWR – 8,800 minimum				
Eight foot straight side bed				
Automatic transmission with overdrive				
Power Steering				
Power four wheel anti-lock brakes				
Power door locks				
Power windows				
Single rear wheel				
Full size spare mounted under bed.				
Anti-spin rear differential				
All season M/S radial tires, black side wall				
Trailer tow package with class IV receiver hitch, standard 7 flat pin wiring connector.				
Four wheel drive chassis with all required components, electronic shift on dash				
Regular cab				
OEM Integrated brake controller				
Interior Components				
Full, insulated rubber flooring-black				
Heated exterior rear view mirrors				
Day/Night interior rear view mirror				
Tow mirrors, power adjustable				
2 extra keys per vehicle, (Three complete sets of keys and remotes as applicable)				
AM/FM radio w/digital clock, blue tooth				
Rear window electronic defroster				
Driver/Passenger air bags				
Upfitter switches with required harness				
Intermittent windshield wiper system				
Interior trim package to include insulating headliner, full door panels, dome light, cloth upholstery treated to resist stains, dark gray color				
Standard tinted windshield				
Air conditioning with all required options				
Tilt steering column				
Cruise control				
Circuit Boss – Circuit Isolator # 70207 (7 circuits), Painless is the current product line we use configured as follows: Circuit 1-3 – constant power Circuit 4-7 - ignition powered To be mounted behind kick panel under steering column.				
12V separately fused power port				
Weather Tech Floorliner floor mats-black				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
Body				
Full front bumper				
Engine block heater 110V				
Rear step bumper				
Front tow hooks				
Vertex VTX609A amber led strobes one on each corner incorporated into turn signal and reverse lamp compartments, wired into same circuit and switch as Whelen warning lights				
Back-up warning device, 97 dB				
Day time running lights				
Whelen R1LPP-A warning light to be mounted, on an Acari light mount, wired to dash mounted switch and Circuit 1 on Circuit Boss, constant hot circuit				
ECCO 3315 amber arrow stick, mounted below the top light mount attached to Acari mount, constant hot circuit				
Gall wing door cross box tool box, diamond tread plate, aluminum, full extra wide, Weather Guard				
Exterior color to be BRIGHT WHITE				
Snow plow prep package				
Tommy Liftgate, 1300 lb G2-54-1342 EA27				
9' power V front steel plow with quick hitch mount, plow lights, rubber deflector, LED lighting, hydraulic plow lift, dual trip edge and plow side marker flags. 9.2, 9.6 both acceptable, red paint. Boss preferred.				
Factory mounted tubular nerf bar, wheel to wheel stainless steel or aluminum				
Factory splash guards				
9" Gamber-Johnson console box MCS-EPIC9. Compartment configured as follows: Top(dash side) – two way radio Motorola XPR series (city will have installed after delivery) Second compartment – Arrow Stick controller Bottom compartment Console to be mounted as centered as possible on transmission hump. Blanks shall be supplied to blank remaining openings.				
Full front bumper				
Manuals				
Full set of repair and parts manuals				
Warranty				
Full factory standard warranty				
Electrical Connections all connections must meet this standard minimum				
All lighting used shall be, at a minimum, a two (2) wire light grounded through a wired connection to the battery system.				
Wiring shall be run in loom where exposed, and have grommets or other edge protection where wires pass through metal.				
Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids. Electrical wiring and equipment shall be installed utilizing the following guidelines:				
All wire ends not placed into connectors shall be sealed with a heat shrink end cap. Wires without a terminating connector or sealed end cap shall not be allowed.				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
All holes made in the roof shall be caulked with silicon (no exception).				
Corrosion preventative compound shall be applied to non-waterproof electrical connectors located outside of the cab or body. All non-waterproof connections shall require this compound in the plug to prevent corrosion and for easy separation of the plug.				
Any lights containing non-waterproof sockets in a weather-exposed area shall have corrosion preventative compound added to the socket terminal area.				
Rubber coated metal clamps shall be used to support wire harnessing and battery cables routed along the chassis frame rails.				
Heat shields shall be used to protect harnessing in areas where high temperatures exist. Harnessing passing near the engine exhaust shall be protected by a heat shield				
For ease of identification, battery cables shall be color coded. All positive battery cables shall be red in color or wrapped in red loom the entire length of the cable. All negative battery cables shall be black in color				
Wire connections shall be made using crimp style heat shrink butt splice connectors or soldered connection covered with heat shrink. If crimp style connector is used, crimping tool Westward 13H876 or equivalent must be used to prevent piercing heat shrink. Solder sleeve butt splice type connectors shall not be allowed.				

Description	Quantity	Unit Price	Extended Price
Firm Fixed Price for 3/4 Ton Regular Cab Pick-Up Truck per the specifications	2	\$	\$

Cab and Chassis Manufacturer/Model _____ Model Year _____

Estimated Delivery Time Upon Receipt of Purchase Order _____ Calendar Days

Dealer Name _____

NOTE: The Bid MUST be submitted by a licensed vehicle dealer in the State of Iowa

Dealer Representative Signature _____ Date _____

DELIVERY ADDRESS
 Joy Huber
 Fleet Services Division
 500 15th Avenue SW
 Cedar Rapids, IA 52404

BILLING ADDRESS
 Finance Department – Accounts Payable
 City of Cedar Rapids
 101 1st Street SE
 PO Box 2148
 Cedar Rapids, IA 52406-2148