

**ATTACHMENT E - BID SUBMITTAL FORM**  
**¾ Ton Pick-Up Trucks – RFB #PUR0817-030**

**SPECIFICATION COMPLIANCE – Any supplier who willfully falsifies responses indicating compliance or non-compliance with the minimum requirements listed below will be subject to suspension and/or debarment from bidding.**

One (1) new ¾ Ton Regular Cab Chassis with Service Body, model year 2017 or 2018

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>Drive Train</b>				
8 cylinder 6.0L or greater				
Wheelbase 133", CA 56"				
GVWR – 8,800 lb minimum				
Chassis-cab package to allow for service body				
Automatic transmission with overdrive				
Power Steering				
Power four wheel disc anti-lock brakes				
Power door locks				
Power windows				
Full size spare mounted under bed				
Anti-spin rear differential				
All season M/S radial tires, black side wall				
Trailer tow package with class IV receiver hitch, standard 7 pin wiring connector.				
Four wheel drive chassis with all required components, electronic shift on dash				
Regular cab				
OEM Integrated brake controller				
Single rear wheel				
Snow plow prep package				
<b>Interior Components</b>				
Full black rubber mat flooring-black				
Heated exterior rear view mirrors				
Day/Night interior rear view mirror				
Tow mirrors, power adjustable				
2 extra keys per vehicle, ( <b>Three</b> complete sets of keys and remotes as applicable)				
AM/FM radio w/digital clock, Bluetooth				
Rear window electronic defroster				
Driver/Passenger air bags				
Side curtain air bag system				
Intermittent windshield wiper system				
Interior trim package to include insulating headliner, full door panels, dome light, vinyl upholstery, dark gray.				
Upfitter switches with required harness				
Standard tinted windshield				
Air conditioning with all required options				
Tilt steering column				
Electronic speed control				
12V separately fused power port				
Laptop computer stand consisting of the following components: Gamber Johnson –TabCruzer Mini universal tablet mount 7160-0774 Quick adjustable 12 upper pole with height-QADJ-UPPER-L 13" lower tube-DS-LOWER-13				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
Vehicle specific bottom mount Short support brace 7160-0230 Clevis Tile/Swivel 7160-0419				
2000 Watt Tripp Lite Inverter controlled on/off by upfitter switch with GFCI outlet in curbside horizontal compartment. Inverter installed in cab behind passenger seat with on/off ran by ignition circuit. Vehicle must be running when using inverter to keep battery charged.				
WeatherTech black molded floor mats				
<b>Body</b>				
Full front chrome bumper				
Engine block heater 110V				
Front tow hooks				
Back-up warning device, 97 dB				
Day time running lights				
Vertex VTX609A amber led strobes one on each corner incorporated into turn signal and wired into same circuit and switch as Whelen warning lights, 12 volt constant				
Whelen R1LPP-A warning light to be mounted, on an Acari light mount, wired to dash mounted switch, 12 volt constant				
ECCO 3315 Traffic advisor mounted to Acari mount below Whelen R1LPPA light, 12 volt constant				
9' power V front steel plow with quick hitch mount, plow lights, rubber deflector, and plow side marker flags, LED lighting, hydraulic plow lift and dual trip edge. 9.2, 9.6 both acceptable, red paint. Boss preferred.				
VMAC 70 CFM air compressor with cooler, accessories should be included in rear box such as air reel				
Factory mounted tubular nerf bars, stainless or aluminum				
Factory splash guards				
Exterior color to be <b>BRIGHT WHITE</b>				
<b>Manuals</b>				
Full set of repair and parts manuals				
<b>Warranty</b>				
Full factory standard warranty				
<b>Electrical Connections</b> all connections must meet this standard minimum				
All lighting used shall be, at a minimum, a two (2) wire light grounded through a wired connection to the battery system.				
Wiring shall be run in loom where exposed, and have grommets or other edge protection where wires pass through metal.				
Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids. Electrical wiring and equipment shall be installed utilizing the following guidelines:				
All wire ends not placed into connectors shall be sealed with a heat shrink end cap. Wires without a terminating connector or sealed end cap shall not be allowed.				
All holes made in the roof shall be caulked with silicon (no exception).				
Corrosion preventative compound shall be applied to non-waterproof electrical connectors located outside of the cab or body. All non-waterproof connections shall require this				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
compound in the plug to prevent corrosion and for easy separation of the plug.				
Any lights containing non-waterproof sockets in a weather-exposed area shall have corrosion preventative compound added to the socket terminal area.				
Rubber coated metal clamps shall be used to support wire harnessing and battery cables routed along the chassis frame rails.				
Heat shields shall be used to protect harnessing in areas where high temperatures exist. Harnessing passing near the engine exhaust shall be protected by a heat shield				
For ease of identification, battery cables shall be color coded. All positive battery cables shall be red in color or wrapped in red loom the entire length of the cable. All negative battery cables shall be black in color				
Wire connections shall be made using crimp style heat shrink butt splice connectors or soldered connection covered with heat shrink. If crimp style connector is used, crimping tool Westward 13H876 or equivalent must be used to prevent piercing heat shrink. Solder sleeve butt splice type connectors shall not be allowed.				

### 56" Service Body

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>General</b>				
56" CA Single Rear Wheel Knapheide service body				
Overall width 82.75"				
Overall Length 96"				
Aluminum front rock guards				
Mud flaps				
Rear grab handles				
Standard shelving package for compartments				
E track on inside of cargo area. Upper and Lower E Track both sides				
72" long x 8" tall x width of compartment top aluminum shovel baskets on curb side and street side placed one foot back from rear window.				
One piece molded doors with automotive grade finish inside and out				
Recessed door jambs				
Stainless steel fasteners throughout the body				
Steel understructure				
Standard white finish				
Vinyl covered cable door stops on all compartments				
Street side front Vertical compartment to have hooks				
Curbside horizontal compartment to have outlet				
Rain diverters on compartment doors				
LED exterior Light Package and License Plate Mount to meet FMVSS 108. All wiring to be installed in conduit or loom application. All connections are to be secured and sealed.				
Tommy Liftgate, 1300 lb G2-54-1342 EA27				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
<b>Compartment Lighting</b>				
Flex tube lighting in each compartment with one master on/off switch in cab of truck, upfitter switch, 12 volt constant				
<b>Warning Lights</b>				
Two Whelen 4" rear surface mount LED strobes on service body, amber, 12 volt constant				
Acari light mount on cab with one Whelen R1LPP-A, Vertex VTX609A amber strobes mounted in the clear lens front corners of the chassis. All switched to one upfitter switch, 12 volt constant				

Description	Quantity	Firm Fixed Price
Firm Fixed Price for one (1) 3/4 Ton Regular Cab Chassis with Service Body per the specifications	1	\$

Cab and Chassis Manufacturer/Model \_\_\_\_\_ Model Year \_\_\_\_\_

Service Body Manufacturer/Model \_\_\_\_\_

Estimated Delivery Time Upon Receipt of Purchase Order \_\_\_\_\_ Calendar Days

Dealer Name \_\_\_\_\_

NOTE: The Bid MUST be submitted by a licensed vehicle dealer in the State of Iowa

Dealer Representative Signature \_\_\_\_\_ Date \_\_\_\_\_

**DELIVERY ADDRESS**  
 Joy Huber  
 Fleet Services Division  
 500 15<sup>th</sup> Avenue SW  
 Cedar Rapids, IA 52404

**BILLING ADDRESS**  
 Finance Department – Accounts Payable  
 City of Cedar Rapids  
 101 1<sup>st</sup> Street SE  
 PO Box 2148  
 Cedar Rapids, IA 52406-2148