

ATTACHMENT C – BID SUBMITTAL FORM

Half-Ton Pickup Truck with Boxes – RFB #PUR1217-101

SPECIFICATION COMPLIANCE - Any supplier who willfully falsifies responses indicating compliance or non-compliance with the minimum requirements listed below will be subject to suspension and/or debarment from bidding.

Specifications for Half-Ton SuperCab Pickup Truck with 6.5' bed with boxes for the Water Plant.

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
Drive Train				
5.3L gasoline engine minimum				
Wheelbase 141" minimum				
GVWR – 5,500 minimum				
6.5 foot straight side bed				
Automatic transmission with overdrive				
Power Steering				
Power four wheel disc anti-lock brakes				
Power door locks				
Power windows				
Full size spare mounted under bed.				
Anti-spin rear differential				
All terrain radial tires, black side wall				
Trailer tow package with class IV receiver hitch, 2" shaft. Standard 7 flat pin wiring connector.				
Four wheel drive chassis with all required components, electronic shift on the dash				
Integrated brake controller				
Interior Components				
Full rubber mat flooring, black				
Heated exterior rear view mirrors				
Day/Night interior rear view mirror				
2 extra keys per vehicle, (Three complete sets of keys and remotes as applicable)				
AM/FM radio w/digital clock, bluetooth				
Driver/Passenger air bags				
Side curtain air bag system				
Intermittent windshield wiper system				
Interior trim package to include insulating headliner, full door panels, dome light, vinyl upholstery dark gray				
Standard tinted windshield				
Air conditioning with all required options				
Tilt steering column				
Electronic speed control				
12V separately fused power port				
Circuit Boss – Circuit Isolator # 70207 (7 circuits), Painless is the current product line we use configured as follows: Circuit 1-3 – constant power Circuit 4-7 - ignition powered To be mounted behind kick panel under steering column				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
WeatherTech molded floor mats				
Body				
SuperCab				
Full front bumper				
Engine block heater 110V				
Rear step bumper				
Back-up warning device, 97 dB				
Day time running lights				
Rear sliding rear window if available				
Vertex VTX609A amber led strobes one on each corner incorporated into turn signal and reverse lamp compartments, wired into same circuit and switch as Whelen warning lights				
Whelen R1LPP-A warning light to be mounted, on an Acari light mount, wired to dash mounted switch and Circuit 1 on Circuit Boss				
72" Brute High Capacity TopSider w/drawers Part ID TBS400-72BD on drivers side (American Van)				
Contractor TopSider w/drawer TBS200-48-BD mounted under ladder rack on passenger side, 48" (American Van)				
Front and rear tow hooks				
Angled ladder rack full length of pack with appropriate locking device				
Splash guards, front and rear				
Wheel to wheel running boards				
Exterior color to be BRIGHT WHITE				
Manuals				
Full set of repair and parts manuals				
Warranty				
Full factory standard warranty				
Electrical Connections (all connections must meet this standard minimum)				
All lighting used shall be, at a minimum, a two (2) wire light grounded through a wired connection to the battery system.				
Wiring shall be run in loom where exposed, and have grommets or other edge protection where wires pass through metal.				
Exterior exposed wire connectors shall be positive locking, and environmentally sealed to withstand elements such as temperature extremes, moisture and automotive fluids. Electrical wiring and equipment shall be installed utilizing the following guidelines: All wire ends not placed into connectors shall be sealed with a heat shrink end cap. Wires without a terminating connector or sealed end cap shall not be allowed.				

Minimum Specification	Does Not Meet Spec	Meets Spec	Exceeds Spec	Comments
All holes made in the roof shall be caulked with silicon (no exception).				
Corrosion preventative compound shall be applied to non-waterproof electrical connectors located outside of the cab or body. All non-waterproof connections shall require this compound in the plug to prevent corrosion and for easy separation of the plug.				
Any lights containing non-waterproof sockets in a weather-exposed area shall have corrosion preventative compound added to the socket terminal area.				
Rubber coated metal clamps shall be used to support wire harnessing and battery cables routed along the chassis frame rails.				
Heat shields shall be used to protect harnessing in areas where high temperatures exist. Harnessing passing near the engine exhaust shall be protected by a heat shield				
For ease of identification, battery cables shall be color coded. All positive battery cables shall be red in color or wrapped in red loom the entire length of the cable. All negative battery cables shall be black in color				
Wire connections shall be made using crimp style heat shrink butt splice connectors or soldered connection covered with heat shrink. If crimp style connector is used, crimping tool Westward 13H876 or equivalent must be used to prevent piercing heat shrink. Solder sleeve butt splice type connectors shall not be allowed.				

Pricing	Quantity	Firm Fixed Unit Price
Firm Fixed Price for Half-Ton Pickup Truck with Boxes	1	\$

Manufacturer: _____ Model: _____ Model Year: _____

Estimated lead time for delivery upon receipt of purchase order: _____ calendar days

Dealer Name: _____

NOTE: All bids MUST be submitted by a licensed vehicle dealer in the State of Iowa

Dealer Representative Signature: _____ Date: _____

DELIVERY ADDRESS:

Joy Huber
City of Cedar Rapids Fleet Services Division
500 15th Avenue SW
Cedar Rapids, IA 52404

BILLING ADDRESS:

Finance Department – Accounts Payable
City of Cedar Rapids
101 First Street SE, PO Box 2148
Cedar Rapids, IA 52406-2148