



DESIGN

Product Type:	Broadloom
Construction:	Tufted
Minimum Sq. Yd.:	No Minimum
Surface Texture:	Textured Heathered Looped
Gauge:	1/10 (39.37 rows per 10 cm)
Density:	7,037
Weight Density:	182,977
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Finished Pile Thickness:	.133" (3.38 mm)
Dye Method:	Solution Dyed
Backing Material:	Unibond® Plus
Fiber Type:	Colorstrand® SD Nylon
Face Weight:	26.0 oz. per sq. yd. (882 g/m ²)
Pattern Repeat:	None
Width:	12' width (3.66 m)
Soil Release Technology:	Sentry Soil Protection
Foot Traffic Recommendation TARR:	Heavy

SUSTAINABILITY

IAQ Green Label Plus:	Green Label Plus 3802
Pre-Consumer Recycled Content:	40%
NSF 140:	Gold
Declare Label:	Declared Red List Free

PERFORMANCE

Static:	AATCC-134 Under 3.5 KV
Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450

SERVICE

Warranties:	Lifetime Limited Unibond® Plus Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



374
Terra Clay




559
Anodized Lapis



589
Celestial



679
Blarney Stone



689
Forest



719
Carbon Char



837
Biscotti Crunch



879
Earth



928
Majolica Tin



948
Quartz



964
Smokestack



965
Steel



978
Mineralite



989
Onyx